

## « Z » LOCKER



Ref. 113.X7 from the company SUFFIXE (70190 Rioz, phone: 03 84 91 24 70).

### **Quantity :**

In function of the architect drawings

### **Technical data:**

Standard dimensions of the columns: height : 183,5 cm + feet 15 cm – depth 50 cm – width 35 or 40 cm per column

The lockers are entirely build in solid grade laminate (frame and doors) of 10 mm thickness, adjusted to the humid atmosphere.

The assembly go very fast: it just need to insert and then screw the laminate panel (floor, shelves and upper parts). It is possible to gather it in the factory (as an option).

The assembly is done by block, from 1 to 4 columns which allow to build complete furniture.

The hinges are in stainless steel and are set up at the right side of the standard column.

The shelves are put with a 2% slope which evacuate the wash water from the front.

The fastenings are also in stainless steel and are invisible in the frontage. The lockers are put down on rectangular anodized stringers (50x30 mm) which are supported on nylon adjustable feet

(attended by fiberglass) or set on a masonry base.

You can add in option numbers on each doors.

**In general:**

●Each box is set up with a hanger bar and 2 shelves.

●Choice of the locking system:

1 user with key locker (2 keys per lock), door padlock or code lock.

Several user with code lock or change lock.

(If you need other kind of lock, feel free to contact us)

●Lockers colors

The colors available are in function of the architect choice, following Suffixe color chart (20 choice of colors).

**In option:**

- White base to handle the simple locker (ref. 227.11) or double side (ref 227,12)

Dimensions : height 35 cm – bench overhanging 35 cm – length from 60 cm to 3 m by slice of 30 and 40 cm.

- The roof is angled in solid grade laminate.
- The fanlight is also in solid grade laminate.